

DCN-DISCS Discussion Unit with Channel Selector



The Discussion Unit with Channel Selector enables participants to speak, register a request-to-speak and listen to the speaker. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has a built-in channel selector that makes it suitable for discussions in which more than one language is used and simultaneous interpretations are available. The channel selector includes two up and down channel select keys and a display showing the number and the abbreviation of the languages, enabling rapid selection of the required language channel.

Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when microphone is on)
- The built-in loudspeaker speaker is muted when the microphone is on to prevent acoustic feedback.
- A variety of rims (DCN-DISR, to be ordered separately) are available, so the unit can be matched to the interior
- The unit can be used a delegate unit or as a chairman unit (DCN-DISBCM chairman buttons, to be ordered separately)
- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)
- The unit is available in light and dark colored bases

- Low susceptibility to mobile phone interference
- Compact, attractive and ergonomic design
- Pluggable microphone
- Channel selector with number and abbreviated channel name
- Built-in loudspeaker
- Usable as delegate or chairman unit

Controls and Indicators

- Alphanumeric display for language channel selection with number and abbreviated channel name
- Socket for pluggable microphones (DCN-MICS or DCN-MICL)
- Microphone button with a red, green or yellow illuminated ring. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphones have volume control buttons
- Recessed 'De-init' switch

Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) stereo jack type headphones sockets
- 2 m (78.7 in) cable terminated with in a molded six-pole circular connector.
- Six-pole circular connector for loop-through connections

Certifications and Approvals

Region	Certification
Europe	CE

Technical Specifications

Electrical

Color top

Color base

DCN-DISCS-L DCN-DISCS-D

Frequency response	30 Hz to 20 kHz		
Headphone load impedance	> 32 ohm < 1k ohm		
Output power	2 x 15 mW/32 ohm		
Mechanical			
Mounting	Tabletop (portable or fixed mounting) and flush mounting		
Dimensions (H x W x D)	(without microphone)		
Tabletop	61 x 190 x 116 mm (2.4 x 7.5 x 4.6 in)		
Flush mounted	6 x 190 x 120 mm (0.2 x 7.5 x 4.7 in)		
Weight	800 g (1.76 lb)		

Silver (RAL 9022)

Light Grey (RAL 000 7500)

Charcoal (PH 10736)

Ordering Information

DCN-MICL Pluggable Long Microphone length 480 mm (18.9 inch), silver	DCN-MICL		
DCN-DISCLM Cable Clamp (25 pcs)	DCN-DISCLM		

25 pieces

Ordering Information				
DCN-DISCS-L Discussion Channel Selector Light pluggable microphone, light base, microphone and rims to be ordered separately	DCN-DISCS-L			
DCN-DISCS-D Discussion Channel Selector Dark pluggable microphone, dark base, micro- phone and rims to be ordered separately	DCN-DISCS-D			
Accessories				
DCN-MICS Pluggable Short Microphone length 310 mm (12.2 inch), silver	DCN-MICS			
DCN-DISR-D Rim Dark (10 pcs) dark, 10 pieces	DCN-DISR-D			
DCN-DISBCM Buttons Chairman (10 sets) 10 sets	DCN-DISBCM			
DCN-DISBDD Buttons Dual Use (10 sets) 10 sets	DCN-DISBDD			
DCN-DISRMH Rim Metal High Gloss (10 pcs) metal, high gloss, 10 pieces	DCN-DISRMH			
DCN-DISR-SR Rim Silver (10 pcs) silver, 10 pieces	DCN-DISR-SR			
DCN-DISRMS Rim Metal Semi Gloss (10 pcs) metal, semi gloss, 10 pieces	DCN-DISRMS			
DCN-DISRH-SR Rim High Gloss Silver (10 pcs) silver, high gloss, 10 pieces	DCN-DISRH-SR			

Americas: Bosch Communications Systems 12000 Portland Avenue South Burnsville, Minnesota, 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschcommunications.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Bosch Security Systems Pte Ltd 38C Jalan Pemimpin Singapore 577180 Phone: +65 6319 3450 Fax: +65 6319 3459 apr.security.ystems@bosch.com www.boschsecurity.com

Represented by

@ Bosch Security Systems Inc. 2008 | Data subject to change without notice T2697844875 | Cur: en-US, V11, 8 Dec 2008