

# **EASY AV-R Conventional In-built Strobe for SG 200**




- ► Quick installation
- ► No additional wiring or power supply necessary
- ► Extremely low power consumption
- Two flash frequency and light intensity (brightness) levels can be selected (set via jumper)


The EASY AV-R Conventional In-built Strobe is installed in the SG 200 Sounder to enable an additional visual alarm. The EASY AV-R is suitable for all variants of the SG 200 and its predecessor, the SG 100.

# **System Overview**

#### View 1



# View 2



# **Certifications and Approvals**

Region	Certification	
Europe	CE	Easy AV-R
Russia	GOST	POCC DE.C313B06300

#### **Parts Included**

## **Quantity Components**

1 EASY AV-R Conventional In-built Strobe for SG 200, red, with seal ring

#### **Technical Specifications**

#### **Electrical**

Operating voltage	10 V DC to 32 V DC
Current consumption	3 mA to 10 mA
Light intensity	
- High	3.6 cd
- Low	1.8 cd

# 2 | EASY AV-R Conventional In-built Strobe for SG 200

#### Mechanics

Material	PC (UL94 V-0)
Color	Red, transparent
Weight	73 g

#### **Environmental conditions**

mounted cable feed

Permissible operating temperature -25 °C to +70 °C Protection class as per EN 60529

SG 100 / SG 200 with surface-mounted cable feed SG 100 / SG 200 with flush- IP 54

#### **Special features**

Flash frequency	1 Hz / 1.5 Hz
Light intensity	1.9 cd / 3.6 cd
Flash strength	Approx. 1 W / 2 W
Light color (wave length)	Red, 625 nm to 640 nm

## **Ordering Information**

## **EASY AV-R Conventional In-built Strobe for** SG 200

**EASY AV-R** 

Red strobe for retrofitting to SG 200 Sounder and SG 100 previous model

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

F.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Represented by