

3M™ RFID Handheld Tracker

The 3M™ Handheld Tracker is a lightweight portable device that expands the capabilities of the 3M™ RFID File Tracking System. The Handheld Tracker scans files in file rooms, individual offices, common work areas, boxes and virtually anywhere files are stored. Compact and easy to use, the Handheld Tracker can hold information on more than one million items. The ergonomic design and swivel antenna maximize comfort and minimize stooping. No more bending or stretching to read high or low shelves. And because it simultaneously performs shelf-reading, searching and inventory scans, it can save time, increase productivity and discover errors that might otherwise go unnoticed.

Functions:

File Inventory

- Expedites inventory management
- Scans and stores file locations
- Imports inventory data into the 3M RFID File Tracking System software
- Updates current file locations in the database

Shelf Order

- Notifies the user of files that are out of order
- Gives the correct shelf location of misplaced files

Item searches

- Search lists can be created to identify specific files
- Search lists can be exported from the software to the Handheld Tracker
- Visual and auditory signals during scans notify the user when files have been located

Features:

Easy to use


- Ideal for shelf-reading, re-shelving, searching, and exception-finding
- Simultaneously performs shelf-reading, searching and inventory scans
- Increases productivity and creates a more orderly office

Ergonomic, Handheld Design

- Comfortable
- Cordless
- Compact
- Lightweight

High Storage Capacity

- Holds information for more than one million items.
- Stores information effectively and easily



Specifications

Operating Temperature	Typical ambient temperature range: 50°F to 104°F (10°C to 40°C)
Storage Temperature	-40°F to 131°F (-40°C to 55°C)
Humidity	0% to 85% RH, non-condensing
Memory Card	Type I or Type II CompactFlash™ card (A 64-MB memory card stores data for approximately 460,000 items.)
Battery Type	Only use a Molicel MCR-1821 battery.
Battery Charger	Only use a Molicel MAC-1821B battery charger.
Typical Charge Life	A fully charged battery will last for approximately three to four hours of "trigger time" (time the trigger is pressed or activated). This typically provides many hours (even a full day or two) of use before recharging is required.
Typical time to fully charge a battery	The battery charger will charge a fully discharged battery in approximately four hours.
Battery Charge Power	100-240 Vac, 1.0A, 50-60 Hz
Read Range	Up to 8 in.
Dimensions	Handheld unit: 9.5" x 7" x 4" (240 mm x 180 mm x 100mm) Antenna portion: 9.5" x 4" x 0.5" (240 mm x 100 mm x 12.5 mm)
Weight (Approximate)	Handheld unit: 25 oz (700 g) Shipping container weight: 11 lbs (5Kg)



3M Track and Trace Solutions

3M Center Building 225-4N-14
St. Paul, MN 55144-1000
USA
1-800-944-3512
www.3M.com/RFID

Please recycle. Printed in U.S.A.
© 3M 2008. All rights reserved.
3M is a trademark of 3M
75-0500-6845-3

Shelving images provided by Spacesaver Corporation
© 2008 Spacesaver Corporation.
Spacesaver Corporation is a division of KI.
KI and Spacesaver are registered trademarks of Krueger International, Inc.